


130V-010

Shape and size



Model	A	B	C	D	Lead.
	max.	max.	max	Type	Φ
130V-010	7.4mm	12.7mm	3.8mm	5.1	0.60

Lead wire material: tin-plated metal wire, $\Phi 0.60\text{mm}$.

Encapsulation material: Flame-retardant epoxy powder, meeting UL94V-0 requirements

Electrical performance

Maximum overload current	$3A_{AC}$	Maximum voltage	$130V_{AC}$
Maximum non-operating current $25^{\circ}\text{C}\pm 2^{\circ}\text{C}$	100mA	Minimum operating current 25°C	200mA
Starting zero-power resistor	2.5-9.0 Ω	Maximum resistance one hour after action	20 Ω

Testing conditions and delivery standards

Inspection items	Test	Delivery standard
Starting zero-power resistor	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, Place in the air	2.5-9.0 Ω
Non-operating current	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 100mA, Maintain 60min	Non-operating
Typical action time	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 500mA	Less than 6S
Motion durability	130V, 3A, 15min	No open flame or burning

Working temperature : -40 to 85

Packaging conditions: 1000pcs per bag