


130V-015

Shape and size



Model	A	B	C	D	Lead.
	max.	max.	max	Type	Φ
130V-015	7.4mm	13.0mm	3.8mm	5.1	0.60

Lead wire material: tin-plated metal wire, $\Phi 0.60\text{mm}$.

Encapsulation material: Flame-retardant epoxy powder, meeting UL94V-0 requirements

Electrical performance

Maximum overload current	$3A_{AC}$	Maximum voltage	$130V_{AC}$
Maximum non-operating current $25^{\circ}\text{C}\pm 2^{\circ}\text{C}$	150mA	Minimum operating current 25°C	300mA
Starting zero-power resistor	2.5-7.5 Ω	Maximum resistance one hour after action	18 Ω

Testing conditions and delivery standards

Inspection items	Test	Delivery standard
Starting zero-power resistor	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, Place in the air	2.5-7.5 Ω
Non-operating current	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 150mA, Maintain 60min	Non-operating
Typical action time	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 750mA	Less than 5.5s
Motion durability	130V, 3A, 15min	No open flame or burning

Working temperature : -40 to 85

Packaging conditions: 1000pcs per bag