


130V-110

Shape and size



Model	A	B	C	D	Lead.
	max.	max.	max	Type	Φ
130V-110	14.5mm	19.6mm	3.8mm	5.1mm	0.80mm

Lead wire material: tin-plated metal wire, $\Phi 0.80\text{mm}$.

Encapsulation material: Flame-retardant epoxy powder, meeting UL94V-0 requirements

Electrical performance

Maximum overload current	$10A_{AC}$	Maximum voltage	$130V_{AC}$
Maximum non-operating current $25^{\circ}\text{C}\pm 2^{\circ}\text{C}$	1.1A	Minimum operating current 25°C	2.2A
Starting zero-power resistor	0.20–0.65 Ω	Maximum resistance one hour after action	1.2 Ω

Testing conditions and delivery standards

Inspection items	Test	Delivery standard
Starting zero-power resistor	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, Place in the air	0.20–0.65 Ω
Non-operating current	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 1.10A, Maintain 60min	Non-operating
Typical action time	$25^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 5.5A, 12V	Less than 6.3s
Motion durability	130V, 7A, 15min	No open flame or burning

Working temperature : -40 to 85

Packaging conditions: 500pcs per bag