


72V-200

Shape and size



Model	A	B	C	D	E	Lead.
	max.	max.	max	$\pm 0.75\text{mm}$	Min	Φ
72V-200	17.8mm	22.9mm	3.0mm	5.1	7.6mm	0.80

Lead wire material: tin-plated metal wire, $\Phi 0.80\text{mm}$.

Encapsulation material: Flame-retardant epoxy powder, meeting UL94V-0 requirements

Electrical performance

Maximum overload current	$40A_{DC}$	Maximum voltage	$72V_{DC}$
Maximum non-operating current $25^{\circ}\text{C} \pm 2^{\circ}\text{C}$	2.0A	Minimum operating current 25°C	4.0A
Starting zero-power resistor	0.07–0.14 Ω	Maximum resistance one hour after action	0.21 Ω

Testing conditions and delivery standards

Inspection items	Test	Delivery standard
Starting zero-power resistor	$25^{\circ}\text{C} \pm 2^{\circ}\text{C}$, Place in the air	0.07–0.14 Ω
Non-operating current	$25^{\circ}\text{C} \pm 2^{\circ}\text{C}$, 2.0A, Maintain 60min	Non-operating
Typical action time	$25^{\circ}\text{C} \pm 2^{\circ}\text{C}$, 10.0A, 12V	Less than 8S
Motion durability	72V, 40A, 24hr	No open flame or burning

Working temperature : -40 to 85

Packaging conditions: 500pcs per bag